

SHEEP HOCK and TONGUE BONE CUTTER

Models 525-1 and 525-TB



The Jarvis Models 525-1 and 525-TB - hydraulic powered hock and tongue bone cutter for sheep.

JARVIS

- The 525-1 and 525-TB are best suited for sheep hock and tongue bone cutting. The Model 525-1 is also suitable for beef tail removal and poultry neck cutting.
- Compact for easy maneuverability; robust for long, trouble-free operation.
- Super fast cutting cycle combined with high cutting force means high performance for the most demanding applications.
- Dual trigger controls for operator safety.
- Constructed from corrosion resistant materials for optimum hygiene.
- Meets national and international requirements for hygiene and safety.



POWERFUL - ROBUST - COMPACT

SHEEP HOCK and TONGUE BONE CUTTER

Models 525-1 and 525-TB

Specifications

Drive	Hydraulic
-------	-----------

Models 525-1 and 525-TB

Capacity		720 / hour
Cutting Cycle Time		0.6 sec
Cutting Force	1425 lbf	6.34 kN
Control Handle		
Pneumatic Single / Dual Trigger	100 psi	6.9 bar
Pneumatic Dual Anti-tie Down	50 psi	3.4 bar
Blade Opening		
525-1	1.5 in	38.1 mm
525-TB	1.73 in	43.9 mm
Overall Length		
525-1	15.3 in	389 mm
525-TB	13.3 in	338 mm
Weight	9 lbs	4.1 kg

Hydraulic Power Unit

Motor Power	5 hp	3729 W
Operating Voltage	460 / 230 V, 3 phase, 60 Hz other voltages and 50 Hz available	
Hose Length	16 ft	4.9 m
Oil Capacity	20 gal	76 L
Overall Dimensions (l x w x h)	31.8 x 25.1 x 29.9 in	808 x 638 x 759 mm
Weight	250 lbs	113 kg
Oil Viscosity at 100° F / 40° C	200 SUS	46 ISO

Equipment Selection and Accessories		Order Number
Model 525-1	Single Acting Dual Triggers	4025077
	Single Acting One Trigger ("CE" version)	4025078
	Double Acting Dual Trigger	4025107
Model 525-TB	Double Acting Dual Triggers	4025099
Hydraulic Power Unit	460 / 230 V, 3 phase, 60 Hz	4027293
	440 / 415 / 380 / 220 V, 3 phase, 50 Hz	4027214
Balancer		4042044
Blade		
525-1		1023412
525-TB		1023561



Products for the meat and poultry industry

Jarvis Products Corporation · 33 Anderson Road · Middletown, CT 06457-4926 · United States of America
 Telephone (860) 347-7271 · Fax (860) 347-9905 · sales@jarvisproducts.com · www.jarvisproducts.com