

HYDRAULIC BREAKING SAW

Model HBS 1000



The Jarvis Model HBS 1000 - hydraulic powered circular breaking saw.

- The HBS 1000, with a 4.75 inch (121 mm) depth of cut, is ideally suited for:
 - Beef: chucks, shoulders, ribs, forequarters, chine bones, briskets, loins and aitch bones.
 - Pork: chine bone and ham marking.
- High powered (5.5 hp) hydraulic motor - no bogging down, no motor icing and low noise.
- Short overall length and specially designed handles for easy handling.
- Smooth surface construction for easy cleaning and optimum hygiene.
- Anti-tie down controls for operator safety.
- Meets national and international requirements for hygiene and safety.

JARVIS

ULTIMATE POWER - EXCELLENT HANDLING

HYDRAULIC BREAKING SAW

Model HBS 1000

Specifications

Drive	hydraulic
-------	-----------

Model HBS 1000

Motor Power	5.5 hp	4100 W
Blade Speed at 5.5 gpm / 20.8 Lpm		1925 rpm
Control Handle		dual / electric
Blade Diameter	10.5 in	267 mm
Cutting Depth (maximum)		
with 10.5 in / 267 diameter mm blade	4.75 in	121 mm
Overall Length	34 in	864 mm
Weight	31 lbs	14 kg
Vibration	less than (<) 124 dB	<1.58 m / sec ²
Noise (one meter from tool)		92 dB

Hydraulic Power Unit

Motor Power	7.5 hp	5593 W
Operating Voltage	460 / 230 V, 3 phase, 60 Hz	
	other voltages and 50 Hz available	
Hose Length	16 ft	5 m
Oil Capacity	30 gal	113.6 L
Oil Viscosity at 100° F / 40° C	200 SUS	46 ISO
Oil Flow Rate	5.5 gal / min	20.8 L / min
Overall Dimensions (l x w x h)	38 x 32 x 34 in	965 x 813 x 864 mm
Weight	405 lbs	183.7 kg

Equipment Selection and Accessories

Order Number

Model HBS 1000		
	with 10.5 in / 267 diameter mm blade	4007042
Hydraulic Power Unit	with hydraulic hoses and control box	
	460 / 230 V, 3 phase, 60 Hz	4027064
Blades		
	10.5 in / 267mm diameter blade - 150 teeth	1023474
	10.5 in / 267 mm skip tooth diameter blade - 84 teeth	1023111
Balancer		4042046



Products for the meat and poultry industry

Jarvis Products Corporation · 33 Anderson Road · Middletown, CT 06457-4926 · United States of America
 Telephone (860) 347-7271 · Fax (860) 347-9905 · sales@jarvisproducts.com · www.jarvisproducts.com