

CIRCULAR BREAKING SAW

Model SEC 230-4, SEC 230-4LN



**The Jarvis Model SEC 230-4 -
electrically powered circular breaking saw.**

JARVIS

- The SEC 230-4, with a 3 inch (76 mm) depth of cut, is ideally suited for:
 - Beef: cutting chucks, shoulders, ribs, forequarters, hindquarters, chine bones, briskets and loins.
- Sealed, 2.25 hp electric motor for ultimate performance.
- Short overall length and specially designed handles for easy handling.
- Features electric or mechanical braking.
- Smooth surface construction for easy cleaning and optimum hygiene.
- Anti-tie down controls for operator safety.
- Meets national and international requirements for hygiene and safety.



SMOOTH - POWERFUL - RUGGED

CIRCULAR BREAKING SAW

Model SEC 230-4, SEC 230-4LN

Specifications

Drive	Electric
-------	----------

Model SEC 230-4, SEC 230-4LN

Motor Power	2.25 hp	1678 W
Operating Voltage	415 / 400 / 230 / 115 / 42 V, 3 phase, 50 Hz	
Blade Speed	575 / 480 / 380 / 240 / 208 V, 3 phase, 60 Hz	
50 Hz		1350 rpm
60 Hz		1650 rpm
Control Handle	Electric Dual Anti-tie Down or One Trigger (CE)	
Brake	Electric (DC) or Mechanical	
Blade Diameter	9.1 in	231 mm
Cutting Depth (maximum)	3.0 in	76 mm
Overall Length	24 in	610 mm
Weight	40 lbs	18.1 kg
Vibration	less than 108 dB	<0.25 m / sec ²
Noise (one meter from tool)		less than 80 dB

Equipment Selection and Accessories	Order Number
-------------------------------------	--------------

Model Sec 230-4	
42 V, 3 phase, 50 Hz with DC brake	4004218
42 V, 3 phase, 50 Hz with mechanical brake	4004206
115 V, 3 phase, 50 Hz with mechanical brake	4004246
230 V, 3 phase, 50 Hz with mechanical brake	4004207
240 V, 3 phase, 60 Hz with mechanical brake	4004215
240 V, 3 phase, 60 Hz with DC brake	4004217
380 V, 3 phase, 50 Hz with mechanical brake	4004205
480 V, 3 phase, 60 Hz with DC brake	4004216
480 V, 3 phase, 60 Hz with mechanical brake	4004214

Model Sec 230-4LN	
42 V, 3 phase, 50 Hz with DC brake	4004221
42 V, 3 phase, 50 Hz with mechanical brake	4004224
240 V, 3 phase, 60 Hz with DC brake	4004220
240 V, 3 phase, 60 Hz with mechanical brake	4004223
480 V, 3 phase, 60 Hz with DC brake	4004219
480 V, 3 phase, 60 Hz with mechanical brake	4004222

Blades <i>Please specify blade preference when ordering.</i>	
9.1 in / 231 mm diameter - 130 teeth	1023286
9.1 in / 231 mm diameter, Skip Tooth - 72 teeth	1023387
9.1 in / 231 mm diameter, Noise Reduction - random skip tooth	1023299
9.1 in / 231 mm diameter, Noise Reduction - 60 teeth	1023348

Balancer	4042035
----------	---------



Products for the meat and poultry industry

Jarvis Products Corporation · 33 Anderson Road · Middletown, CT 06457-4926 · United States of America
 Telephone (860) 347-7271 · Fax (860) 347-9905 · sales@jarvisproducts.com · www.jarvisproducts.com